

Pole Banner Select is a double-sided, durable, blockout banner material designed for indoor or outdoor applications. The material offers a matte finish and is ideal for application where complete opacity is required. Pole Banner Select is compatible with solvent, eco-solvent and UV ink. Available in widths from 38” - 196”.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Total Weight	DIN53352 BS3424 Method 5A	610 gsm	18 oz./yd ²
Denier		840 x 840 D	
Base Fabric		Polyester	
Thickness	DIN EN ISO 2286-3	0.46 mm	
Tensile Strength	DIN53352 BS 3424	1350 x 1200 N/5cm	154.17 x 137.04 lbs/in
Tear Strength (warp/weft)	DIN53356 BS3424	245 x 185 N	55 185x 41.59 lbs
Adhesion	DIN53357 BS3425	60 N/5CM	6.85 lbs/in
Temperature Resistance	DIN53357 BS3425 Method 10	- 20 – 70 °C	

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications		■	■	■		■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■				

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60, 3.20,	38”, 54”, 63”, 126”

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. A weight variance of +1/-2 is acceptable. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)