

KODAK PROFESSIONAL

Inkjet Artist Canvas, Matte / 410g

High-quality canvas, fine-art results

Water-resistant matte finish

KODAK PROFESSIONAL Inkjet Artist Canvas, Matte is a medium textured, 2-over-1 weave, poly/cotton blend canvas that features a water-resistant matte finish.

The latest printer and ink technology

This high-quality canvas is perfect for fine art and photographic reproductions utilizing the lateste dye and pigmented inks.

APPLICATIONS:

- · Gallery wraps
- Mounted canvas prints
- Fine art reproduction

FEATURES:

- Poly/cotton blend canvas
- Medium textured, 2-over-1 weave
- · Compatible with dye and pigment inks

US Size	Euro Size	Quantity	SKU
17" x 40'	43,2 cm x 12,19 m	1 Roll	KPROTMC17
24" × 40'	61,0 cm x 12,19 m	1 Roll	KPROTMC24
36" x 40'	91,4 cm x 12,19 m	1 Roll	KPROTMC36
44" x 40'	111,8 cm x 12,19 m	1 Roll	KPROTMC44
60" x 40'	154,2 cm x 12,19 m	1 Roll	KPROTMC60



KODAK PROFESSIONAL

Inkjet Artist Canvas, Matte / 410g

Properties	Specifications	
Material	65% polyester, 35% cotton base	
Fabric Weave	2 x 1 weave	
Gauge	18 mil	
Base Weight	410g	
Whiteness	>100 CEI	
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.	
Software Setting	The coating is engineered for more than 300% ink coverage. A Heavy Weight Coated or Enhanced Matte setting is recommended as a starting point. However, a custom ICC profile is ideal for optimal results.	
Light Fastness	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.	
Optimal Service Environment	66-77° F , 20-60% R.H.	
Finishing/Post Processing	No post processing or finishing is required, though a clear fixative may be applied to enhance certain areas of the print.	
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.	
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging	
Shelf Life	1 year from the BMG ship date when stored in proper conditions.	



AMS: 888-893-4668 EMEA: +34 935 479 700 APJ: +61 2 8038 5013

KodakWFMedia.com

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2022, Brand Management Group

